



Generating Set Performance		50 Hz	
SERVICE		Continuous Service	Intermittent Service
Rated output	kVA	41	45
Active power output *	kW	33	36
Rated speed	r.p.m.	1,500	
Standard Voltage	V	400 / 230	
Voltage available	V	230 / 132	

Performance data refers to Standard Reference Conditions of ISO 8528 : + 25 °C , 100 m ALT, relative humidity 30 %

During running-in period the output increases by approx. 5 % which is taken into consideration at delivery.

Prime Mover Performance		1.500 r.p.m.	
SERVICE		Continuous Service	Intermittent Service
Rated output	kW (CV)	37.7 (51.2)	41.4 (56.3)
Manufacturer		YANMAR	
Engine model		4TNV 98T GGE	
4 stroke Diesel Engine - Injection type		DIRECT	
Aspiration type		TURBO	
Cylinders, number and arrangement		4 - L	
Bore x stroke	mm	98 x 110	
Total displacement	L	3.318	
Cooling system		WATER	
Lube oil specifications		API (CF, CF-4, CI-4); ACEA (E-3, E-4, E-5)	
Specific fuel consumption	Lts./h	10.25	
Specific oil consumption (at full load)		-	
Compression ratio		18.1	
Lube oil maximum capacity	L	10.5	
Lube oil minimum capacity	L	4.5	
Speed governor	Type	Mechanical	
Air filter	Type	Medium Dry Type	

PRIME POWER (P.R.P.): The prime power is the maximum power available with varying loads for an unlimited number of hours. The average power output during a 24h period of operation must not exceed 80% of the declared prime power between the prescribed maintenance intervals and at standard environmental conditions. A 10% overload is permissible for 1 hour every 12 hours of operation.

STAND BY POWER: Is the maximum power available for a period of 500 hours/year with a mean load factor of 90% of the declared stand-by power. No kind of overload is permissible for this use.

Synchronous Generator *		
Poles	N°	4
Winding connections (standard)		Star - series
Frame mounting		SAE 3 11 1/2"
Insulation	class	H
Enclosure (according to IEC-34-5)		IP 23
Phases		3 + N
Voltage regulator		A.V.R. (electronic)
Steady State voltage		within ± 1.5% from no load to full loading with p.f 0.8

*Alternator used by HIMOINSA Gensets meet the requirements of following Standard: IEC 34-1; CEI 2-3; ; VDE 0530; BS 4999-5000:NF 51-100,11



Generating Set Installation Data		1.500 rpm
EXHAUST SYSTEM		
Max. exhaust temperature at full load	° C	480
	° F	896
Exhaust gas flow	m ³ /min	10.42
Heat rejected to exhaust	Kcal/Kwh	-
Maximum allowed back pressure	mm / H2O	1,207.05
AIR REQUIREMENT		
Air requirement for combustion at 100% load / rated speed	m ³ /min	3.88
	ft ³ /min	137.02
ELECTRIC STARTING SYSTEM		
Starting motor output	kW	1,4
	CV	1,9
Minimum recommended battery capacity	Ah	92
Auxiliary voltage	Vcc.	12
LIQUID CAPACITY		
Lube oil system including sump, filters, etc.	L	10,50
FUEL TANK CAPACITY		
Open Skid Genset	L	115
Soundproofed	L	66
SOUND EMISSION LEVEL (Soundproofed gensets)		
1 Metre (Free Field)	dB (A)	69
7 Metre (Free Field)	dB (A)	62

Generating Set transport data		
WEIGHT AND DIMENSIONS OPEN SKID GENSET		
Length	m - ft	1.62 - 5.23
Width	m - ft	0.75 - 2.46
Height	m - ft	1.31 - 4.30
Shipping volume seaworthy (Standard supplier)	m ³ - ft ³	1.12 - 3.95
Dry weight (with standard accessories)	kg - lb	626 - 1,377 *
WEIGHT AND DIMENSIONS SOUNDPROOFED		
Length	m - ft	2.25 - 7.38
Width	m - ft	1.05 - 3.44
Height	m - ft	1.45 - 4.75
Shipping volume seaworthy (Standard supplier)	m - ft	3.42 - 120.59
Dry weight (with standard accessories)	kg - lb	1,081 - 2,378.2 *

* Weights and dimensions based on standard product configuration (this information could change for optional configurations)

Local distributor

